





DIMENSIONS TECHNICAL DATA

300mmØ x 90mm depth

Total lumens: 1200 Colour temp: 3,000K

Power supply: 220-240V, Double Insulated

CRI: 80 Wattage: 13.5 Control gear: Included

FEATURES

• Interchangeable covers click onto the main body

Covers supplied separately Covers available in 3 colours; Charcoal, Silver or White

LK3050 body Supplied in silver only

- · Can be wall or ceiling mounted
- Microwave/ occupancy/ light SENSOR: 360° detection angle
 Adjustable detection range from 1 to 8

Time setting adjustable 10sec to 12min Lux detection adjustable 10 to 2000 lux **SPECIFICATIONS**

Lamp included: No Number of lamps: 1

IP Rating: IP65

Technology field: LED

Indoor / Outdoor: Indoor, Outdoor

Mounting type: Ceiling, Wall

Colour: Silver/Grey

De	tection A	Area	
Switch	1	Up Down	
100%	Up		
75%	Up		
50%	Down	Up	
10%	Down	Down	

Daylight Sensor					
Switch	5	6			
Disable	Up	Up			
50 Lux	Up	Down			
10 Lux	Down	Up			
2 Lux	Down	Down			

Hold Time					
Switch	3	4			
5 seconds	Up	Up			
90 seconds	Up	Down			
5 minutes	Down	Up			
15 minutes	Down	Down			

1	2	3	4	5	6	
						↑ Up
						↓ Down

Use this guide to set switches 1,2,3,4,5 & 6 to up or down to your desired requirements