

**Diffuser Optimised 18W LED Downlight**  
**Model: LDL175-WH**



DIMENSIONS	TECHNICAL DATA	FEATURES	SPECIFICATIONS
Flange 198mmØ Hole cut: 175 Cavity depth: 180 Side clearance: 20	Total lumens: 1560 Colour temp: 4,000K Power supply: 220-240V, Double Insulated CRI: 81 Wattage: 18 Beam angle: 60° Control gear: Included	<ul style="list-style-type: none"><li>• Optimised Non Glare Downlights</li><li>• LED's set back and anti glare baffle for low glare U.G.R.</li><li>• Aluminium body - forward traveling heat sinking to dissipate heat below the ceiling to ensure optimum life</li><li>• Samsung brand LED technology</li><li>• Integral driver for easy installation</li><li>• Quick and economical installation, only one connection - large looping mains terminals</li><li>• beam angle 60 degrees and with extra spill light for good general room lighting.</li><li>• Equivalent to 2 x 18Watt CFL downlight</li><li>• 248lux at 1.5metres</li><li>• 96lux at 2.4metres</li></ul>	CA90 Material: Aluminium Lamp included: Yes Number of lamps: 1 Air / Moisture Transfer: Closed IP Rating: IP44 Technology field: LED Indoor / Outdoor: Indoor Mounting type: Ceiling, Recessed Colour: White

