



Trim 94mmØ Total lumens: 500 CA135 Hole cut: 75 Colour temp: 3,000K Lamp included: Yes Cavity depth: 190 Power supply: 220-240V, Double Insulated Lamp holder type: MR16 Side clearance: 50 CRI: 90 Number of lamps: 1 Wattage: 7 Technology field: Halogen, LED Replaceable Beam angle: 36° Indoor / Outdoor: Indoor Control gear: Included Mounting type: Ceiling, Recessed	DIMENSIONS	TECHNICAL DATA	SPECIFICATIONS
Cavity depth: 190 Power supply: 220-240V, Double Insulated Lamp holder type: MR16 CRI: 90 Number of lamps: 1 Wattage: 7 Technology field: Halogen, LED Replaceable Beam angle: 36° Indoor / Outdoor: Indoor	Trim 94mmØ	Total lumens: 500	CA135
Side clearance: 50 CRI: 90 Number of lamps: 1 Wattage: 7 Technology field: Halogen, LED Replaceable Beam angle: 36° Indoor / Outdoor: Indoor	Hole cut: 75	Colour temp: 3,000K	Lamp included: Yes
Wattage: 7 Technology field: Halogen, LED Replaceable Beam angle: 36° Indoor / Outdoor: Indoor	Cavity depth: 190	Power supply: 220-240V, Double Insulated	Lamp holder type: MR16
Beam angle: 36° Indoor / Outdoor: Indoor	Side clearance: 50	CRI: 90	Number of lamps: 1
		Wattage: 7	Technology field: Halogen, LED Replaceable
Control gear: Included Mounting type: Ceiling, Recessed		Beam angle: 36°	Indoor / Outdoor: Indoor
		Control gear: Included	Mounting type: Ceiling, Recessed