



DIMENSIONS	TECHNICAL DATA	FEATURES	SPECIFICATIONS
<ul style="list-style-type: none"><li>• 115mmØ x 120mmH</li></ul>	<p>Total lumens: 950</p> <p>Colour temp: 3,000K</p> <p>Power supply: 220-240V</p> <p>CRI: 80</p> <p>Wattage: 10</p> <p>Beam angle: 45°</p> <p>Control gear: Included</p>	<ul style="list-style-type: none"><li>• 10Watt Integral LED.</li><li>• 45° beam angle with spill light out to 90°.</li><li>• Integral driver in base.</li><li>• Dimmable with Trailing edge and Universal dimmers.</li><li>• Dims down to 20% of light output.</li><li>• Less than 19% glare.,Compliant to UGR &lt;19 Standard.</li><li>• Specified by Superlux to ensure quality light output &amp; dimming.</li><li>• Available in Black with Silver Reflector or White with White Reflector. Other colour reflectors are available to be purchased separately.</li></ul>	<p>Material: Aluminium body, Plastic reflector</p> <p>Lamp included: Yes</p> <p>Number of lamps: 1</p> <p>IP Rating: IP54</p> <p>Technology field: LED</p> <p>Indoor / Outdoor: Indoor</p> <p>Mounting type: Ceiling</p> <p>Colour: White</p>



LDLS115-WH with LDLSREF-SI optional extra Silver reflector accessory.



LDLS115-WH with LDLSREF-GD optional extra Gold reflector accessory.