

Energy Saver Fluorescent Downlight in Satin Chrome
Model: SD125F-SC



DIMENSIONS	TECHNICAL DATA	FEATURES	SPECIFICATIONS
• 145mmØ x 153mmH - Hole cut: 125 - Cavity depth: 180 - Side clearance: 25	Total lumens: 840 Colour temp: 2,700K Power supply: 220-240V Dimmable: Yes CRI: 80 Wattage: 15 Max	• 14Watts of Power = 100Watts of Illuminance • DEDICATED LAMP - GLS lamps will not fit into the SD125F • DEDICATED QUALITY - of light same output as GLS lamps and warm colour rendering. • DEDICATED REFLECTOR - is designed to optimise self ballasted lamp characteristics. • Moisture Transfer Classification - Closed. Sealed construction preventing access of insects and drafts through ceilings. • Thermal Insulation Classification - Abutted. Ceiling insulated (zero rated) may be abutted up against the SD125 for maximum insulation effectiveness. • Lamp not exposed in ceiling cavity. • Thermal cut-off and auto reset function for protection against misuse and overloading. • (RW) STC sound transmission rating.	CA80 Lamp included: Yes Lamp holder type: E27 Number of lamps: 1 Air / Moisture Transfer: Closed Technology field: Fluorescent Indoor / Outdoor: Indoor Mounting type: Ceiling, Recessed Colour: Satin Chrome

