

Integral Design Fixed MR16 Downlight in Satin Chrome  
Model: SVE75-SC



DIMENSIONS	TECHNICAL DATA	FEATURES	SPECIFICATIONS
<ul style="list-style-type: none"><li>• Trim 94mmØ.</li></ul> Hole cut: 75 Cavity depth: 190 Side clearance: 50	Total lumens: 525 Colour temp: 3,000K Power supply: 220-240V Dimmable: Yes CRI: 100 Wattage: 35 Beam angle: 38°	<ul style="list-style-type: none"><li>• Thermal cut-off protection with auto reset function. Guards against installation faults or overlamping.</li><li>• Quick and economical installation - only one connection large looping mains terminal.</li><li>• Acoustic rating: for acoustic STC 55 ceilings space 1.6m minimum.</li><li>• For acoustic (RW) STC 57 and 58, space 2.5m minimum.</li><li>• Superlux recommends the use of trailing edge dimmers.</li><li>• HIH (High Intensity Halogen) lamp included, 30% power saving. 35W = 50W of illuminance.</li><li>• 5 year transformer warranty.</li><li>• ECG must not be installed on a circuit with inductive loads.</li></ul>	Lamp included: Yes Lamp holder type: MR16 Number of lamps: 1 Air / Moisture Transfer: Closed Technology field: Halogen, LED Replaceable Indoor / Outdoor: Indoor Mounting type: Recessed Colour: Satin Chrome