

Integral Design Fixed MR16 Downlight in White
Model: SVE75-WH



DIMENSIONS	TECHNICAL DATA	FEATURES	SPECIFICATIONS
<ul style="list-style-type: none">• Trim 94mmØ. Hole cut: 75 Cavity depth: 190 Side clearance: 50	Total lumens: 525 Colour temp: 3,000K Power supply: 220-240V Dimmable: Yes CRI: 100 Wattage: 35 Beam angle: 38°	<ul style="list-style-type: none">• Thermal cut-off protection with auto reset function. Guards against installation faults or overlamping.• Quick and economical installation - only one connection large looping mains terminal.• Acoustic rating: for acoustic STC 55 ceilings space 1.6m minimum.• For acoustic (RW) STC 57 and 58, space 2.5m minimum.• Superlux recommends the use of trailing edge dimmers.• HIH (High Intensity Halogen) lamp included, 30% power saving. 35W = 50W of illuminance.• 5 year transformer warranty.• ECG must not be installed on a circuit with inductive loads.	Lamp included: Yes Lamp holder type: MR16 Number of lamps: 1 Air / Moisture Transfer: Closed Technology field: Halogen, LED Replaceable Indoor / Outdoor: Indoor Mounting type: Recessed Colour: White