

Model: KL10

10 W LED Exterior Spotlight

superlux
we engineer light

Specifications:

Colour Temperature 5,000K

Ingress Protection is IP54

Total lumens output 650 lumens

220-240 Volt 50 Hz power supply, Class 1



Mounting: Wall or under eave mount.

Important: This unit should be installed by a registered electrician.

1. Ensure the power supply is isolated before installation
2. Once the best mounting position is chosen, remove the 2 acorn nuts and seal washers from the base and remove the backplate. Put the spotlight carefully to one side
3. Fix the back plate in place by passing the supply cord through the grommet hole and mount the backplate to the wall or eave with 2 suitable screws.
4. Connect the wiring:
 - Phase to **L**
 - Neutral to **N**
 - Earth wire to

Important:

- Use sealant around the 2 mounting screws to ensure the spotlight remains watertight
 - Seal the cable in grommet with silicon if necessary, to prevent water ingress at cable
 - Ensure the Neoprene 'o'-ring seal is in place.
5. Reassemble the sensor light to the backplate with the 2 seal washers & acorn nuts.
 6. Adjust aim of the LED spot head, **Ensure you loosen the wing knob**, before adjusting the LED spotlight head direction. Then tighten up again when you are happy with the position.

Please keep these Instructions for future reference. Do not wash with a hose or water blaster.

