



DIMENSIONS	TECHNICAL DATA	FEATURES	SPECIFICATIONS
• 260mmØ • Post supplied in two segments use one or two for a height of 700mmH or 1160mmH (460mmL extension post available to purchase separately - PV300-POST) • 114mmØ mounting base	Total lumens: 200 Colour temp: 3,000K Power supply: Solar Wattage: 5 Beam angle: 120°	• Part of our Freelite™ Solar Lighting range • A simple 'install and forget' solution to outdoor lighting • Lens and light distribution designed for highlighting gardens and foliage • Post supplied in two segments use one or two for a height of 700mmH or 1160mmH, Optional Accessory 460mmL extension post available to purchase separately - PV300-POST • Can be mounted with supplied base or post can be cast directly into concrete • Autonomously lights from dusk till dawn • Smart Energy Management System gradually steps down light output overnight to provide all-night lighting over 2 to 3 days of cloud • Made with quality Aluminium and UV stabilised Polycarbonate • Solar lighting offers a much cheaper, hassle-free installation compared with traditional lighting. With no trenching, cables, or conduits required, these costs are eliminated • 3 year warranty with expected battery life of 5 to 10 years when well situated - view warranty info here. • Battery replaceable • Find out more about our Freelite™ Solar range here • Not available to purchase in Australia	Material: Aluminium, UV Stabilised Polycarbonate Lamp included: Yes IP Rating: IP65 Technology field: LED Indoor / Outdoor: Outdoor Mounting type: In-Ground, Post Lights



